



AIR CAULKING GUN



AIR CAULKING GUN		Specifications	Recommended Air Pressure 30 ~ 90 psi (2.1-6.3 kg/cm ²) Max. Air Pressure Resistable 150 psi			
Model	Capacity Available (oz)		Specification	For 9 oz Air Caulking Gun.		Packing
	Cartridge	Sachet		Net Weight (kg)	Length (mm)	
GP-853	9		• Steel Tube • No dropping	1.15	310	10 pcs/1.34 cu-ft/G.W.: 14 kgs
GP-853A	9, 11, 13		• w/Air Regulator • Pull Line	0.75	315	10 pcs/1.34 cu-ft/G.W.: 9 kgs
GP-853AS		9, 11, 13, 15	• w/Air Regulator • Pull Line	0.80	315	10 pcs/2.3 cu-ft/G.W.: 10 kgs
GP-853BL	9, 11, 13	9, 11, 13, 15	• w/Air Regulator • Pull Line	0.95	315	10 pcs/2.3 cu-ft/G.W.: 12 kgs
GP-853B	9, 11, 13	9, 11, 13, 15	• w/Air Regulator • Push Rod	0.95	315	10 pcs/2.3 cu-ft/G.W.: 12 kgs
GP-853F	29		• For Construction • Pull Line	1.70	440	10 pcs/2.7 cu-ft/G.W.: 18 kgs
GP-853HR		9, 11, 13, 15	• Light in weight • Push Rod	1.00	325	10 pcs/2.4 cu-ft/G.W.: 12 kgs
GP-853HS		9, 11, 13, 15	• Light in weight • Pull Line	0.90	380	10 pcs/2.3 cu-ft/G.W.: 10 kgs
GP-853H	9, 11, 13		• Light in weight • Pull Line	0.80	380	10 pcs/2.3 cu-ft/G.W.: 9 kgs
GP-853M	9, 11, 13	9, 11, 13, 15	• w/Air Regulator • Push Rod	1.20	380	10 pcs/2.3 cu-ft/G.W.: 13 kgs
GP-853MCL	9, 11, 13	9, 11, 13, 15	• w/Air Regulator & Auto Air Exhaust • Pull Line	0.90	380	10 pcs/2.4 cu-ft/G.W.: 13 kgs
GP-853D	9, 11, 13	9, 11, 13, 15	• w/Spray Nozzle, Fluid Valve & Air Regulator • For Polyurethane and Silicone • Push Rod	1.20	375	10 pcs/2.4 cu-ft/G.W.: 13 kgs
GP-853DC	9, 11, 13	9, 11, 13, 15	• w/Spray Nozzle, Fluid Valve & Auto Air Exhaust • For Polyurethane and Silicone • Push Rod • Pin Regulator	1.20	375	10 pcs/2.4 cu-ft/G.W.: 13 kgs
GP-853MSC	9, 11, 13, 15		• w/Fluid Nozzle & Auto Air Exhaust • For Carpenter & Construction, Galass • Pull Line	1.20	370	10 pcs/2.4 cu-ft/G.W.: 13 kgs