



AIR STRAIGHT DRILL



GP-330



GP-340



GP-330ST



GP-330STN



GP-350



GP-330A

AIR STRAIGHT DRILL		Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm ²)						
Model	Chuck Size	Max. Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-330	3/8"	2,500	1.00	225	0.62	1/4"	6.5	95	< 2.5	20 pcs/1.29 cu-ft/G.W.: 21 kgs
GP-340	3/8"	22,000	0.92	205	0.51	1/4"	6.5	94	< 2.5	20 pcs/1.0 cu-ft/G.W.: 19 kgs
GP-330ST	3/8"	2,600	1.08	218	0.61	1/4"	6.5	82	< 2.5	12 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-330STN	3/8"	3,600	1.08	218	0.64	1/4"	6.5	82	< 2.5	12 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-350	3/8"	1,600	0.87	225	0.23	1/4"	6.5	75	< 2.5	20 pcs/1.1 cu-ft/G.W.: 18 kgs
GP-330A	1/4"	6,500	0.62	175	0.45	1/4"	6.5	85	< 2.5	20 pcs/0.5 cu-ft/G.W.: 15 kgs



AIR ANGLE DRILL



GP-835TB



GP-835ADS



GP-835C



GP-835F



GP-836C

AIR ANGLE DRILL

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Chuck Size	Max. Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-835TB	3/8"	1,900	0.96	220	0.59	1/4"	6.5	92	< 2.5	20 pcs/1.40 cu-ft/G.W.: 21 kgs
GP-835ADS	3/8"	1,800	1.17	200	0.63	1/4"	6.5	82	< 2.5	12 pcs/0.8 cu-ft/G.W.: 15 kgs
GP-835C	3/8"	2,400	1.10	170	0.51	1/4"	6.5	82	< 2.5	10 pcs/0.75 cu-ft/G.W.: 12 kgs
GP-835F	3/8"	2,200	1.20	172	0.52	1/4"	6.5	83	< 2.5	10 pcs/1.73 cu-ft/G.W.: 13 kgs
GP-836C	1/2"	800	1.45	203	0.70	1/4"	6.5	90	< 2.5	10 pcs/0.92 cu-ft/G.W.: 18 kgs



AIR REVERSIBLE ANGLE DRILL



ROTARY AIR HAMMER DRILL



GP-836D



GP-840A



GP-840S



• Composite
GP-840J



• Hammer / Impact Type
GP-19DH

SDS plus



• Hammer / Impact Type
GP-26DH

SDS plus



• Vacuum Suction Fixing Base
• Hammer / Impact Type
GPD-231A

SDS plus

AIR REVERSIBLE ANGLE DRILL

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Chuck Size	Max Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-836D	1/2"	800	1.45	230	0.70	1/4"	6.5	82	< 2.5	10 pcs/0.92 cu-ft/G.W.: 18 kgs
GP-840A	3/8"	2,300	1.30	191	0.56	1/4"	6.5	83	< 2.5	10 pcs/0.73 cu-ft/G.W.: 15 kgs
GP-840S	3/8"	1,800	1.20	177	0.56	1/4"	6.5	87	< 2.5	10 pcs/1.73 cu-ft/G.W.: 13 kgs
GP-840J	3/8"	1,800	0.90	165	0.80	1/4"	6.5	86	< 2.5	10 pcs/0.8 cu-ft/G.W.: 13 kgs

ROTARY AIR HAMMER DRILL

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Chuck Size	Max Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-26DH	SDS-plus	2,100 ~ 3,800	5.88	380	0.80	3/8"	10	83	3.6	4 pcs/1.50 cu-ft/G.W.: 28.6 kgs
GP-19DH	SDS-plus	3,500 ~ 6,500	3.54	250	0.73	1/4"	6.5	89	2.7	6 pcs/1.73 cu-ft/G.W.: 22.5 kgs
GPD-231A	SDS-plus	1,500	10.17	630	0.56	1/4"	6.5	92	-	1 pc/2.1 cu-ft/G.W.: 15 kgs



HEAVY DUTY AIR DRILL



• Reversible Type
• Keyless Chuck
GP-840B



• Keyless Chuck
GP-840C



• Reversible Type
GP-835G
GP-835GR



• Reversible Type
GP-836G
GP-836GR



• Keyless Chuck
GP-835B



• Keyless Chuck
GP-836B3, B5, B8



• Reversible Type
• Keyless Chuck
GP-836E2, E4, E8



• Reversible Type
• Gear Mechanism
GP-26D

HEAVY DUTY AIR DRILL

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Chuck Size	Max. Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-840B	3/8"	1,800	1.10	195	0.62	1/4"	6.5	90	< 2.5	10 pcs/0.85 cu-ft/G.W.: 14 kgs
GP-840C	3/8"	2,200	1.08	194	0.62	1/4"	6.5	88	< 2.5	10 pcs/0.82 cu-ft/G.W.: 12 kgs
GP-835B	3/8"	3,500	1.12	165	0.53	1/4"	6.5	75	< 2.5	10 pcs/0.82 cu-ft/G.W.: 15.2 kgs
GP-836B3	1/2"	300	1.50	228	0.50	1/4"	6.5	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836B5	1/2"	500	1.50	228	0.50	1/4"	6.5	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836B8	1/2"	850	1.50	228	0.50	1/4"	6.5	90	< 2.5	10 pcs/0.8 cu-ft/G.W.: 14 kgs
GP-836E2	1/2"	250	1.50	229	0.70	1/4"	6.5	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-836E4	1/2"	450	1.50	229	0.70	1/4"	6.5	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-836E8	1/2"	800	1.50	229	0.70	1/4"	6.5	90	< 2.5	10 pcs/0.82 cu-ft/G.W.: 14 kgs
GP-835G	3/8"	2,000	1.25	181	0.79	1/4"	6.5	91	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs
GP-835GR	3/8"	2,000	1.25	181	0.79	1/4"	6.5	91	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs
GP-836G	1/2"	500	1.77	220	0.79	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 20 kgs
GP-836GR	1/2"	500	1.77	220	0.79	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 20 kgs
GP-26D	5/8"	600 ~ 1,000	6.40	380	0.80	3/8"	10	87	< 2.5	4 pcs/1.36 cu-ft/G.W.: 24 kgs