



AIR CHIPPING HAMMER



- Round Shank
GP-891
- Hex. Shank
GP-891H



- Round Shank
GP-892
- Hex. Shank
GP-892H



- Round Shank
GP-893
- Hex. Shank
GP-893H



- Round Shank
GP-894
- Hex. Shank
GP-894H



- Round Shank
GP-895
- Hex. Shank
GP-895H



MINI AIR HAMMER (for Fine Masonry Work, Removing Tile)



- Round Shank (Ø10.2mm)
 - Built-in Air Regulator
- GPW-4500**



- Round Shank (Ø10.2mm)
 - Built-in Air Regulator
- GPW-7000**

AIR CHIPPING HAMMER		Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm ²)								
Model	Stroke Speed (bpm)	Piston Stroke (mm)	Shank Size (mm)		Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
			Ø	⬆								
GP-891/GP-891H	3,600	50	14.95	12.80	2.8	254	0.35	3/8"	8	92	10.4	6 pcs/0.8 cu-ft/G.W.: 21 kgs
GP-892/GP-892H	2,500	25.4	17.30	14.50	6.5	388	0.80	3/8"	8	105	11.0	2 pcs/0.75 cu-ft/G.W.: 15.8 kgs
GP-893/GP-893H	2,300	51	17.30	14.50	7.0	410	0.85	3/8"	8	100	11.0	2 pcs/0.75 cu-ft/G.W.: 16.3 kgs
GP-894/GP-894H	2,200	64	17.30	14.50	7.5	450	0.90	3/8"	8	103	11.0	2 pcs/0.93 cu-ft/G.W.: 17.8 kgs
GP-895/GP-895H	1,800	102	17.30	14.50	8.0	480	0.95	3/8"	8	102	11.0	2 pcs/0.93 cu-ft/G.W.: 18.8 kgs

MINI AIR HAMMER (for Fine Masonry Work, Removing Tile)		Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm ²)						
Model	Stroke Speed (bpm)	Piston Stroke (mm)	Shank Size (mm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Packing
GPW-4500	4,500	36	Ø10.2	0.73	155	0.12	1/4"	6.5	88	20 pcs/1.2 cu-ft/G.W.: 19 kgs
GPW-7000	7,000	36	Ø10.2	0.75	155	0.12	1/4"	6.5	88	20 pcs/1.2 cu-ft/G.W.: 19 kgs



COMPOSITE AIR HAMMER (Low Vibration)



AIR HAMMER



• Round Shank
GP-190CSR
• Hex. Shank
GP-190CSRH



• Round Shank
GP-150
• Hex. Shank
GP-150H



• Round Shank
GP-190
• Hex. Shank
GP-190H



• Round Shank
GP-250CSR
• Hex. Shank
GP-250CSRH



• Round Shank
GP-250
• Hex. Shank
GP-250H



• Round Shank
GP-190C
• Hex. Shank
GP-190CH



• Round Shank
GP-250C
• Hex. Shank
GP-250CH



• Round Shank
GP-150SQ
• Hex. Shank
GP-150SQH
• Round Shank
GP-190SQ
• Hex. Shank
GP-190SQH

COMPOSITE AIR HAMMER (Low Vibration)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Stroke Speed (bpm)	Piston Stroke (mm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-190CSR/GP-190CSRH	3,000	71	1.60	215	0.40	1/4"	6.5	100	7.5	10 pcs/1.6 cu-ft/G.W.: 19 kgs
GP-250CSR/GP-250CSRH	2,100	92	1.90	260	0.45	1/4"	6.5	102	5.5	10 pcs/1.6 cu-ft/G.W.: 23 kgs

AIR HAMMER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Stroke Speed (bpm)	Piston Stroke (mm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-150/GP-150H	4,500	41	1.20	150	0.48	1/4"	6.5	99	15.2	10 pcs/0.8 cu-ft/G.W.: 17 kgs
GP-190/GP-190H	3,200	67	1.60	190	0.42	1/4"	6.5	99	13.7	10 pcs/0.85 cu-ft/G.W.: 20 kgs
GP-250/GP-250H	2,000	89	2.20	250	0.40	1/4"	6.5	96	11.0	10 pcs/0.9 cu-ft/G.W.: 22.5 kgs
GP-190C/GP-190CH	3,500	67	1.50	171	0.42	1/4"	6.5	99	8.4	10 pcs/0.8 cu-ft/G.W.: 16.5 kgs
GP-250C/GP-250CH	2,100	89	2.00	225	0.42	1/4"	6.5	96	13.5	10 pcs/1 cu-ft/G.W.: 21 kgs
GP-150SQ/GP-150SQH	4,500	41	1.36	133	0.48	1/4"	6.5	99	15.0	10 pcs/0.55 cu-ft/G.W.: 13 kgs
GP-190SQ/GP-190SQH	3,000	67	1.59	171	0.42	1/4"	6.5	98	9.0	10 pcs/0.97 cu-ft/G.W.: 18 kgs



AIR NEEDLE SCALER



GP-851A



GP-851B



GP-851D



GP-851P



GP-851G



GP-851H



GP-851H1



GP-851H2

AIR NEEDLE SCALER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Needle (mm x pcs)	Stroke Speed (bpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-851A	3 x 19	3,700	2.60	375	0.21	1/4"	8	106	8.7	6 pcs/0.4 cu-ft/G.W.: 17.5 kgs
GP-851B	3 x 19	3,700	2.60	250	0.21	1/4"	8	106	8.7	6 pcs/1.3 cu-ft/G.W.: 19 kgs
GP-851D	3 x 28	3,000	4.50	480	0.21	1/4"	8	106	18.6	4 pcs/1.7 cu-ft/G.W.: 20 kgs
GP-851P	3 x 28	3,500	3.50	360	0.42	3/8"	8	93	14.6	6 pcs/1.5 cu-ft/G.W.: 24 kgs
GP-851G	3 x 23	3,800	2.70	348	0.35	3/8"	8	92	4.7	6 pcs/1.3 cu-ft/G.W.: 19 kgs
GP-851H	3 x 19	4,000	2.10	325	0.45	1/4"	8	91	14.5	10 pcs/1.5 cu-ft/G.W.: 24 kgs
GP-851H1	3 x 19	4,600	3.20	460	0.42	1/4"	8	97	6.3	6 pcs/1.3 cu-ft/G.W.: 22 kgs
GP-851H2	3 x 19	3,000	2.70	370	0.28	1/4"	8	96	17.9	6 pcs/1.3 cu-ft/G.W.: 19 kgs



AIR NEEDLE SCALER & FLUX CHIPPER



GP-851 2-in-1



GP-851E 2-in-1



• Light & Small
GP-851I 2-in-1

For separate model, please specify N=Needle Scaler F=Flux Chipper



• Light & Small
GP-851JN 2-in-1



• Light & Small
GP-851M

AIR NEEDLE SCALER & FLUX CHIPPER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Needle (mm x pcs)	Stroke Speed (bpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-851	3 x 19 Flux Chipper	4,400	3.00	460	0.45	1/4"	8	96	10.2	6 pcs/0.6 cu-ft/G.W.: 20 kgs
GP-851N	3 x 19 Flux Chipper	4,400	2.84	460	0.45	1/4"	8	96	10.2	6 pcs/0.6 cu-ft/G.W.: 18.5 kgs
GP-851F	3 x 19 Flux Chipper	4,400	2.05	363	0.45	1/4"	8	90	14.5	10 pcs/0.7 cu-ft/G.W.: 22 kgs
GP-851E	3 x 19 Flux Chipper	4,400	2.90	410	0.42	1/4"	8	90	14.5	10 pcs/0.6 cu-ft/G.W.: 17.6 kgs
GP-851EN	3 x 19 Flux Chipper	4,400	2.66	410	0.42	1/4"	8	90	14.5	10 pcs/0.5 cu-ft/G.W.: 16.6 kgs
GP-851EF	3 x 19 Flux Chipper	4,400	1.75	335	0.42	1/4"	8	91	14.5	10 pcs/0.5 cu-ft/G.W.: 19 kgs
GP-851I	3 x 12 Flux Chipper	4,800	1.50	290	0.21	1/4"	8	91	14.5	10 pcs/0.5 cu-ft/G.W.: 16 kgs
GP-851IN	3 x 12 Flux Chipper	4,800	1.30	290	0.21	1/4"	8	91	14.5	10 pcs/0.5 cu-ft/G.W.: 14 kgs
GP-851IF	3 x 12 Flux Chipper	4,800	1.04	230	0.21	1/4"	8	90	14.5	10 pcs/0.5 cu-ft/G.W.: 12 kgs
GP-851JN	3 x 12 Flux Chipper	4,200	1.31	258	0.20	1/4"	6.5	91	14.5	12 pcs/0.65 cu-ft/G.W.: 18 kgs
GP-851J	3 x 12 Flux Chipper	4,200	1.08	258	0.20	1/4"	6.5	91	14.5	12 pcs/0.65 cu-ft/G.W.: 16 kgs
GP-851JF	3 x 12 Flux Chipper	4,200	0.88	225	0.20	1/4"	6.5	91	14.5	12 pcs/0.55 cu-ft/G.W.: 11.5 kgs
GP-851M	3 x 12 Flux Chipper	4,000	1.40	280	0.22	1/4"	6.5	91	14.5	12 pcs/0.5 cu-ft/G.W.: 18.2 kgs



AIR SCALING HAMMER / SCABBLER



• One Head
GP-923



• Triple Heads
GP-923A



• Triple Heads
GP-923B

GP-923 AIR SCALING HAMMER / SCABBLER		GP-923A AIR SCALING HAMMER / SCABBLER		GP-923A AIR SCALING HAMMER / SCABBLER	
Piston Stroke	15 mm	Piston Stroke	22.5 mm	Piston Stroke	26 mm
Stroke Speed	7,200 bpm	Stroke Speed	2,800 bpm	Stroke Speed	2,400 bpm
Net Weight	1.90 kgs	Net Weight	3.90 kgs	Net Weight	4.00 kgs
Length	480 mm	Length	496 mm	Length	550 x 185 x 120 mm
Air Cons.	0.30 m ³ /min	Air Cons.	0.42 m ³ /min	Air Cons.	11.5 m ³ /min
Air Intet	1/4"	Air Intet	3/8"	Air Intet	3/8"
Hose Size	8 mm	Hose Size	8 mm	Hose Size	8 mm
Sound Pressure	90 dBA	Sound Pressure	92 dBA	Sound Pressure	92 dBA
Vibration	35.1 m/sec ²	Vibration	13.3 m/sec ²	Vibration	13.3 m/sec ²
Packing	6 pcs/1 cu-ft/G.W.: 15 kgs	Packing	4 pcs/2.3 cu-ft/G.W.: 20.5 kgs	Packing	4 pcs/2.7 cu-ft/G.W.: 20.5 kgs



AIR CONCRETE BREAKER / ROCK DRILL



GPB-10S



GPB-30S

GPB-10S AIR CONCRETE BREAKER / ROCK DRILL		GPB-30S AIR CONCRETE BREAKER / ROCK DRILL	
Piston Dia.	35 mm	Piston Dia.	40 mm
Piston Stroke	151 mm	Piston Stroke	235 mm
Stroke Speed	1,300 bpm	Stroke Speed	1,000 bpm
Shank Size	26 mm	Shank Size	30 mm
Net Weight	14.10 kgs	Net Weight	24.60 kgs
Length	438 mm	Length	590 mm
Air Cons.	0.99 m ³ /min	Air Cons.	1.19 m ³ /min
Air Inlet	1/2"	Air Inlet	3/4"
Hose Size	1/2"	Hose Size	3/4"
Packing	1 pc/0.7 cu-ft/G.W.: 15.6 kgs (with Chisel)	Packing	1 pc/0.9 cu-ft/G.W.: 26 kgs (with Chisel)


GP-131

GP-300

GAH-15

GP-131 AIR SCRAPER		GP-300 AIR PALM HAMMER NAILER		GAH-15 AUTO AIR PALM HAMMER	
Stroke Speed	4,800 bpm	Capacity	6-16 mm Dia. Nail	Associated	Aluminium
Net Weight	0.70 kgs	Free Speed	1,000 bpm	Hammer Tip	Black - medium hard plastic
Length	248 mm	Net Weight	1.20 kgs	Optional	Steel
Air Cons.	0.30 m ³ /min	Length	125 mm	Hammer Tip	Yellow - hard plastic
Air Inlet	1/4"	Nail Guide	Magnetic		Blue - soft plastic
Hose Size	6.5 mm	Air Cons.	0.22 m ³ /min		Red - ultra soft plastic
Sound Pressure	86 dBA	Air Inlet	1/4"	Net Weight	0.60 kgs
Vibration	26 m/sec ²	Hose Size	6.5 mm	Length	92 mm
Packing	25 pcs/0.84 cu.ft/G.W.: 20 kgs	Packing	10 pcs/0.83 cu-ft/G.W.: 13.5 kgs	Air Cons.	0.28 m ³ /min
				Air Intet	1/4"
				Hose Size	6.5 mm
				Packing	20 pcs/1.4 cu-ft/G.W.: 14.5 kgs



AIR HAMMER KIT

**GP-190K
GP-190HK
GP-250K
GP-250HK**

**GP-150SQK
GP-150SQHK
GP-190SQK
GP-190SQHK**

**GP-190CK
GP-190CHK
GP-250CK
GP-250CHK**


GP-190K / GP-190HK GP-250K / GP-250HK		GP-150SQK / GP-150SQHK GP-190SQK / GP-190SQHK		GP-190CK / GP-190CHK GP-250CK / GP-250CHK	
1 pc	Air Hammer	1 pc	Air Hammer	1 pc	Air Hammer
1 pc	Retainer	1 pc	Retainer	1 pc	Retainer
5 pcs	Chisel (175 mm, Round/Hex.)	5 pcs	Chisel (175 mm, Round/Hex.)	5 pcs	Chisel (175 mm, Round/Hex.)
1 pc	Mini Oiler	1 pc	Plastic Box	1 pc	Plastic Box
1 pc	Nipple				
1 pc	Plastic Box				
Packing		Packing		Packing	
GP-190K/190HK	10 sets/1.8 cu-ft/G.W.: 27 kgs	GP-150SQK/150SQHK	6 sets/2.0 cu-ft/G.W.: 19.4 kgs	GP-190CK/190CHK	6 sets/2.0 cu-ft/G.W.: 20 kgs
GP-250K/250HK	5 sets/1.0 cu-ft/G.W.: 17 kgs	GP-190SQK/190SQHK	6 sets/2.0 cu-ft/G.W.: 20 kgs	GP-250CK/250CHK	6 sets/2.0 cu-ft/G.W.: 22 kgs



HAMMER ACCESSORIES

Attachment for Air Chipping Hammer GP-891 / 891H



Retainer Spring (Close)
S033



Retainer Spring (Open)
S039



Flat Chisel
CHI-01FR Round Shank, 240mm
CHI-01FH Hex. Shank, 220mm



Point Chisel
CHI-01PR Round Shank, 250mm
CHI-01PH Hex. Shank, 215mm

Attachment for Air Chipping Hammer GP-892~895 / 892H~895H



Retainer Sleeve
892023



Flat Chisel
CHI-02FR Round Shank, 260mm
CHI-02FH Hex. Shank, 260mm



Point Chisel
CHI-02PR Round Shank, 260mm
CHI-02PH Hex. Shank, 260mm

Attachment for Air Hammer GP-150 / 190 / 250 Series



Retainer Spring
SQ-001



Zip Retainer Spring
SQ-002



Quick Change Retainer
SQ-003



Needle Scaler Attachment
HNS-01



HPT-04



HPT-05



HPT-09

HPT-04 4 Pcs Chisel		HPT-05 5 Pcs Chisel		HPT-09 9 Pcs Chisel	
HPT-04RS	Round Shank, 125 mm	HPT-05RL	Round Shank, 175 mm	HPT-09R	Round Shank, 175 & 125 mm
HPT-04HS	Hex. Shank, 125 mm	HPT-05RS	Round Shank, 125 mm	HPT-09H	Hex. Shank, 175 & 125 mm
Packing	25 sets/0.4 cu-ft/G.W.: 15 kgs	HPT-05HL	Hex. Shank, 175 mm	Packing	18 sets/0.7 cu-ft/G.W.: 24.5 kgs
M.O.Q.	100 sets	HPT-05HS	Hex. Shank, 125 mm	M.O.Q.	108 sets
		Packing	20 sets/0.4 cu-ft/G.W.: 19 kgs		
		M.O.Q.	100 sets		