



AIR HYDRAULIC RIVETER



GP-101



GP-101A



GP-101H



GP-102



GP-104



GP-500



GP-501



GP-843

AIR HYDRAULIC RIVETER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Traction Power (kg.f)	Stroke Length (mm)	Rivet Nut Nose Piece (mm)	Net Weight (kgs)	Height (mm)	Air Cons. (ltr/cycle)	Air Inlet (PT/NPT)	Hose Size (mm)	Packing
GP-101	1,603	14	2.4, 3.2, 4.0, 4.8, 6.0, 6.4	1.78	272	2.32	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 15 kgs
GP-101A	1,229	14	2.4, 3.2, 4.0, 4.8, 6.0, 6.4	1.56	268	1.48	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 12.5 kgs
GP-101H	1,700	18	2.4, 3.2, 4.0, 4.8, 6.0, 6.4	1.75	298	2.90	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 12.5 kgs
GP-102	1,045	16	2.4, 3.2, 4.0, 4.8	1.50	270	1.48	1/4"	6.5	10 pcs/1.65 cu-ft/G.W.: 19 kgs
GP-104	1,045	16	2.4, 3.2, 4.0, 4.8	1.50	265	1.48	1/4"	6.5	10 pcs/1.65 cu-ft/G.W.: 19 kgs
GP-500	1,250	18	2.4, 3.2, 4.0, 4.8, 5.6, 6.4	2.10	325	3.00	1/4"	6.5	10 pcs/3.3 cu-ft/G.W.: 28 kgs
GP-501	900	16	3.2, 4.0, 4.8	1.50	300	1.40	1/4"	6.5	10 pcs/2.26 cu-ft/G.W.: 22 kgs
GP-843	880	14	2.4, 3.2, 4.0, 4.8	1.80	286	1.48	1/4"	6.5	10 pcs/1.6 cu-ft/G.W.: 19 kgs



AIR HYDRAULIC RIVETER (Vacuum Type)



GP-101V/102V/104V



GP-101SV/102SV/104SV



AIR HYDRAULIC RIVETER KITS



GP-102K/102SK/104K/104SK



GP-843K

AIR HYDRAULIC RIVETER (Vacuum Type)				Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm ²)				
Model	Traction Power (kg.f)	Stroke Length (mm)	Rivet Nut Nose Piece (mm)	Net Weight (kgs)	Height (mm)	Air Cons. (m ³ /min)	Air Inlet (PT/NPT)	Hose Size (mm)	Packing	
GP-101V	1,603	14	2.4, 3.2, 4.0, 4.8, 6.0, 6.4	1.85	272	0.11	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 15 kgs	
GP-102V	1,045	16	2.4, 3.2, 4.0, 4.8	1.56	270	0.11	1/4"	6.5	6 pcs/2.55 cu-ft/G.W.: 12 kgs	
GP-104V	1,045	16	2.4, 3.2, 4.0, 4.8	1.56	265	0.11	1/4"	6.5	6 pcs/2.55 cu-ft/G.W.: 12 kgs	
GP-101SV	915	16	2.4, 3.2, 4.0, 4.8, 6.0, 6.4	1.35	243	0.11	1/4"	6.5	10 pcs/2.55 cu-ft/G.W.: 15 kgs	
GP-102SV	695	16	2.4, 3.2, 4.0, 4.8	1.30	245	0.11	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 15 kgs	
GP-104SV	915	16	2.4, 3.2, 4.0, 4.8	1.25	245	0.11	1/4"	6.5	6 pcs/2.3 cu-ft/G.W.: 15 kgs	

AIR HYDRAULIC RIVETER KITS		Specifications	Recommended Air Pressure 90 psi (6.3 kg/cm ²)	
GP-102K/102SK/104K/104SK			GP-843K	
1 pc	Air Hydraulic Riveter (Please check Air Hydraulic Riveter for specifications)		1 pc	Air Hydraulic Riveter (GP-843)
4 pcs	Nose Piece		4 pcs	Nose Piece
40 pcs	Rivet		40 pcs	Rivet
12 pcs	Spare Parts		12 pcs	Spare Parts
Packing	6 sets/1.65 cu-ft/G.W.: 18 kgs		Packing	8 sets/2.63 cu-ft/G.W.: 25 kgs



COMPOSITE AIR HYDRAULIC RIVETER



GP-240



GP-280A



• Vacuum Type
GP-291A
GP-291B



GP-488
GP-489



• Vacuum Type
GP-488V
GP-489V



SPECIAL AIR HYDRAULIC RIVETER



• Aircraft Rivets
• Special Big Rivets
GP-101EX



• LOCKBOLT (HUCK)
GP-101HU



• MONOBOLT
• T-Rivet
• MAGNA-Lok
GP-101TM

COMPOSITE AIR HYDRAULIC RIVETER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Traction Power (kg.f)	Stroke Length (mm)	Rivet Nut Nose Piece (mm)	Net Weight (kg)	Height (mm)	Air Cons. (m ³ /min)	Air Inlet (PT/NPT)	Hose Size (mm/I.D.)	Packing
GP-240	1,088	19.5	2.4, 3.2, 4.0, 4.8	1.87	301	0.8	1/4"	6.5	5 pcs/2.5 cu-ft/G.W.: 15 kgs
GP-280A	1,682	15.0	4.8, 5.6, 6.4	1.95	306	0.8	1/4"	6.5	5 pcs/2.5 cu-ft/G.W.: 16 kgs
GP-291A	1,816	26.0	6.4, 5.6, 4.8	1.94	325	0.8	1/4"	6.5	6 pcs/4.6 cu-ft/G.W.: 20.4 kgs
GP-291B	2,270	26.0	7.8, 6.4, 5.6, 4.8	2.18	325	0.8	1/4"	6.5	6 pcs/4.6 cu-ft/G.W.: 20.9 kgs
GP-488	1,407	26.0	4.8, 5.6, 6.4	1.77	307	0.8	1/4"	6.5	10 pcs/2.8 cu-ft/G.W.: 22 kgs
GP-488V	1,407	26.0	4.8, 5.6, 6.4	1.88	310	0.8	1/4"	6.5	6 pcs/2.4 cu-ft/G.W.: 12.6 kgs
GP-489	1,723	22.5	4.8, 5.6, 6.4, 7.8	1.74	307	0.8	1/4"	6.5	10 pcs/2.8 cu-ft/G.W.: 22 kgs
GP-489V	1,723	22.5	4.8, 5.6, 6.4, 7.8	1.88	310	0.8	1/4"	6.5	6 pcs/3.4 cu-ft/G.W.: 12.0 kgs

※ Riveting Capacity : for Standard Blind Rivet & Blind Rivet Magnalok / Monbolt / Orlock

SPECIAL AIR HYDRAULIC RIVETER

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Traction Power (kg.f)	Stroke Length (mm)	Capacity(mm)		Rivet Nut Dia. (mm)	Net Weight (kgs)	Height (mm)	Air Cons. (ltr/cycle)	Air Inlet (PT/NPT)	Hose Size (mm/I.D.)	Packing
			Steel	Stainless							
GP-101EX	1,860	23	6.4	6.4	4.8, 6.0, 6.4	3.0	230	2.28	1/4"	6.5	4 pcs/2.3 cu-ft/G.W.: 15 kgs
GP-101TM	1,860	23	6.4	6.4	4.8, 6.0, 6.4	3.0	230	2.28	1/4"	6.5	4 pcs/2.3 cu-ft/G.W.: 15 kgs
GP-101HU	1,860	23	1/4"	1/4"	3/16" or 1/4"	2.9	330	2.28	1/4"	6.5	4 pcs/2.3 cu-ft/G.W.: 15 kgs



AIR PULL NUT SETTER AIR RIVETING NUT TOOL



• Handle Exhaust
GP-836LC



• Handle Exhaust
GP-836LC1



• Side Exhaust
GP-836LC2



GP-836LC3



GP-836LC4



GP-836LC5



• Semiautomatic
GP-101RN



• Automatic
GP-250RM



• Automatic
GP-250RI

AIR RIVETING NUT TOOL

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Optional Pulling Nut (mm)	Mechanism	Free Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Packing
GP-836LC	3, 4, 5, 6, 8	Clutch	2,500	1.30	230	0.42	1/4"	10 sets/0.9 cu-ft/G.W.: 17 kgs
GP-836LC1	3, 4, 5, 6, 3/16", 1/4"	Gear	700	1.20	200	0.35	1/4"	10 pcs/1.7 cu-ft/G.W.: 17 kgs
GP-836LC2	6, 8, 10, 1/4", 5/16", 3/8"	Gear	450	1.80	210	0.42	1/4"	10 pcs/1.7 cu-ft/G.W.: 21 kgs
GP-836LC3	10, 12, 7/16"	Gear	100	1.92	228	0.42	1/4"	10 pcs/1.7 cu-ft/G.W.: 23 kgs
GP-836LC4	3, 4, 5, 3/16"	Gear	3,200	1.48	205	0.42	1/4"	10 pcs/1.7 cu-ft/G.W.: 17.7 kgs
GP-836LC5	6, 8, 1/4", 5/16"	Gear	1,000	1.50	205	0.42	1/4"	10 pcs/1.7 cu-ft/G.W.: 17.9 kgs
GP-101RN	M3, 4, 5, 6, 8, 10, 12	Hydraulic	1650 kg.f	1.55	272	1.5 Liter/Cycle	1/4"	6 pcs/2.3 cu-ft/G.W.: 16 kgs
GP-250RM	M3, 4, 5, 6, 8, 10, 12	Hydraulic	2179 kg.f	2.4	278	2.0 Liter/Cycle	1/4"	5 pcs/2.8 cu-ft/G.W.: 20.3 kgs
GP-250RI	6/32", 8/32", 10/24", 10/32", 1/4"-20, 5/16"-18, 3/8"-16, 1/2"-13	Hydraulic	2179 kg.f	2.4	278	2.0 Liter/Cycle	1/4"	5 pcs/2.8 cu-ft/G.W.: 20.3 kgs

For Aluminum & Steel Nut