



AIR NIPPER



GP-005A



GP-005



GP-010



GP-020



GP-030



GP-040

AIR NIPPER		Specifications		Recommended Air Pressure 90 psi (6.3 kg/cm ²)					
Model	Size (mm)	Net Weight (kgs)	Standard Blade		Air Pressure (kg/cm ²)	Air Cons. (cm ³ /time)	Air Inlet	Hose Size (mm)	Packing
			Wire	Plastic					
GP-005A	20Ø x 126	0.081	S20	*	4-5	35	1/4"	5.0	28 pcs/0.6 cu-ft/G.W.: 5.83 kgs
GP-005	30Ø x 120	0.134	S2	*	4-5	64	1/4"	5.0	28 pcs/0.6 cu-ft/G.W.: 6.95 kgs
GP-010	36Ø x 136	0.189	S4	*	5-6	116	1/4"	6.5	28 pcs/0.6 cu-ft/G.W.: 9.89 kgs
GP-020	45Ø x 170	0.344	S5	FD-6	5-6	230	1/4"	6.5	35 pcs/1.9 cu-ft/G.W.: 21.8 kgs
GP-030	56Ø x 207	0.565	S8P	FD-8P	5-6	584	1/4"	8.0	35 pcs/1.9 cu-ft/G.W.: 36 kgs
GP-040	56Ø x 300	0.897	S8P	FD-8P	5-6	956	1/4"	8.0	20 pcs/1.7 cu-ft/G.W.: 25 kgs

Blade Type	Capacity (mm)		Applied Model
	Copper Wire	Iron Wire	
S20	0.8	0.5	GP-005A
S2	1.0	0.5	GP-005
S4	1.6	1.0	GP-010
S5	2.6	2.0	GP-020
S8P	3.3	2.8	GP-030
	Stainless Steel Wire 2.0		
	Piano Wire 1.2		
S8P	4.8	4.0	GP-040
	Stainless Steel Wire 2.8		
FD-6	5.0 Soft Plastic	4.0 Hard Plastic	GP-020
FD-8P	10.0 Soft Plastic	6.5 Hard Plastic	GP-030
	13.0 Soft Plastic	6.5 Hard Plastic	GP-040

For Non-Insulated Terminal		
Blade Type	Capacity (mm)	Applied Model
A5P	1.25 sq	GP-020
A7P	1.25 sq, 2.0 sq, 5.5 sq	GP-030 GP-040
A7WP-2	1.25~2.0 sq, 2.0~5.5 sq	
A7WP-3	1.25~2.0~5.5 sq	
A7P	8.0 sq	GP-040

For Insulated Terminal		
Blade Type	Capacity (mm)	Applied Model
AR7P	1.25 sq, 2.0 sq, 5.5 sq	GP-030
AR7WP	1.25~2.0 sq, 2.0~5.5 sq	GP-040
AR7P	8.0 sq	GP-040