



PREPARATION UNIT-F.R.L.



GP-815H
GP-816H
GP-817H



GP-818H
GP-819H



GP-815H1
GP-816H1
GP-817H1



GP-814S
GP-815S

※ Features :

- Filter element : 5μ
- Adj. pressure range : 0.5 ~ 8.5 kgf/cm²
- Max. service pressure : 9.9 kgf/cm²
- Operating temp. range : 5 ~ 60°C
- Drain capacity : 80 ml
- Oil capacity : 125 ml
- Recommend lubricant : ISO VG-32

PREPARATION UNIT-F.R.L.

Specifications

Recommended Air Pressure 60 ~ 90 psi

Model	Port Size pt/npt	Max Flow (m ³ /min)	Construction Unit			Packing
			Filter	Regulator	Lubricator	
GP-815H	1/4"	1.75	GP-815HA	GP-815HB	GP-815HC	10 pcs/2.2 cu-ft/G.W.: 22 kgs
GP-816H	3/8"	2.50	GP-816HA	GP-816HB	GP-816HC	10 pcs/2.2 cu-ft/G.W.: 22 kgs
GP-817H	1/2"	3.00	GP-817HA	GP-817HB	GP-817HC	10 pcs/2.2 cu-ft/G.W.: 22 kgs
GP-818H	3/4"	4.60	GP-818HA	GP-818HB	GP-818HC	6 pcs/2.48 cu-ft/G.W.: 27 kgs
GP-819H	1"	5.20	GP-819HA	GP-819HB	GP-819HC	6 pcs/2.48 cu-ft/G.W.: 27 kgs
GP-815H1	1/4"	1.75	GP-815HAB		GP-815HC	12 pcs/1.7 cu-ft/G.W.: 20 kgs
GP-816H1	3/8"	2.50	GP-816HAB		GP-816HC	12 pcs/1.7 cu-ft/G.W.: 20 kgs
GP-817H1	1/2"	3.00	GP-817HAB		GP-817HC	12 pcs/1.7 cu-ft/G.W.: 20 kgs
GP-814S	1/8"	1.00	GP-814SAB		GP-814SC	30 pcs/1.3 cu-ft/G.W.: 20 kgs
GP-815S	1/4"	1.10	GP-815SAB		GP-815SC	30 pcs/1.3 cu-ft/G.W.: 20 kgs