



AIR SCREWDRIVER (Impact Type)



AIR SCREWDRIVER (Slip-Clutch Type)



GP-866



• Quick Change
GP-866Q



GP-802



GP-867



GP-867D



GP-804HP



GP-869



GP-868



GP-861H

AIR SCREWDRIVER (Impact Type)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.lb (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-866	4.0 ~ 5.0	1/4"	8,000	26 (35)	0.68	190	0.31	1/4"	6.5	86	< 2.5	20 pcs/0.70 cu-ft/G.W.: 15.5 kgs
GP-866Q	3.5 ~ 4.5	1/4"	8,000	20 (27)	0.68	190	0.31	1/4"	6.5	86	< 2.5	20 pcs/0.73 cu-ft/G.W.: 16 kgs
GP-867	5.0 ~ 6.0	1/4"	8,500	17.4 (23.5)	1.12	215	0.49	1/4"	6.5	95	< 2.5	20 pcs/1.44 cu-ft/G.W.: 24.5 kgs
GP-867D	5.0 ~ 6.0	1/4"	6,500	36 (48)	1.10	210	0.49	1/4"	6.5	92	< 2.5	20 pcs/1.50 cu-ft/G.W.: 23 kgs
GP-868	6.0 ~ 8.0	1/4"	7,000	148 (200)	1.20	210	0.36	1/4"	6.5	89	< 2.5	20 pcs/1.10 cu-ft/G.W.: 25 kgs
GP-869	6.0 ~ 8.0	1/4"	12,000	74 (100)	0.95	195	0.36	1/4"	6.5	92	< 2.5	20 pcs/1.10 cu-ft/G.W.: 21 kgs



AIR SCREWDRIVER (Shut-Off Type)



GP-861H1



• Stubby Type
GP-861C



• Push Start
• Auto Shut off
• Rear Exhaust
GP-904C
GP-905C
GP-905D



GP-865M



• Push Start
• Auto Shut off
• Rear Exhaust
GP-906A



• Push Start
• Auto Shut off
• Rear Exhaust
GP-906B



AIR SCREWDRIVER (Slip-Clutch Type)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.lb (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-802	5.0 ~ 6.0	1/4"	1,800	3.0 (4)	0.65	210	0.35	1/4"	5.0	84	< 2.5	20 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-804HP	2.2 ~ 3.0	1/4"	1,500	1.5 (2)	0.78	210	0.35	1/4"	5.0	78	< 2.5	20 pcs/1.10 cu-ft/G.W.: 17 kgs
GP-861H	3.0 ~ 4.0	1/4"	1,500	2.2 (3)	0.65	228	0.21	1/4"	5.0	83	< 2.5	20 pcs/1.10 cu-ft/G.W.: 14 kgs
GP-861H1	3.0 ~ 4.0	1/4"	600	5.9 (8)	0.90	228	0.35	1/4"	5.0	83	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-865M	6.0	1/4"	1,700	9.6 (13)	1.16	265	0.48	1/4"	5.0	86	< 2.5	10 pcs/0.60 cu-ft/G.W.: 14 kgs

AIR SCREWDRIVER (Shut-off Type)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-861C	3.0 ~ 4.0	1/4"	1,000	0.39 - 0.78	0.70	230	0.28	1/4"	5.0	86	< 2.5	20 pcs/1.10 cu-ft/G.W.: 16 kgs
GP-904C	3.5	1/4"	1,000	1.20 - 2.20	0.71	229	0.13	1/4"	5.0	75	< 2.5	20 pcs/1.40 cu-ft/G.W.: 14.5 kgs
GP-905C	5.0 ~ 6.0	1/4"	740	3.50 - 7.00	0.95	244	0.20	1/4"	5.0	80	< 2.5	20 pcs/2.00 cu-ft/G.W.: 26.3 kgs
GP-905D	5.0 ~ 6.0	1/4"	450	4.00 - 10.00	0.95	244	0.20	1/4"	5.0	80	< 2.5	20 pcs/2.00 cu-ft/G.W.: 26.3 kgs
GP-906A	2.0	4 mm	2,500	0.20 - 0.35	0.35	180	0.07	1/4"	5.0	69	< 2.5	10 pcs/0.90 cu-ft/G.W.: 5 kgs
GP-906B	2.5	4 mm	800	0.35 - 1.00	0.37	190	0.07	1/4"	5.0	69	< 2.5	10 pcs/0.90 cu-ft/G.W.: 5 kgs



AIR ANGLE SCREWDRIVER (Slip-Clutch Type)



• Side Exhaust
GP-802L90



• Rear Exhaust
GP-804L90



• Handle Exhaust
• Outer Adjustable Clutch
GP-861J



• Handle Exhaust
• Outer Adjustable Clutch
GP-861J1



• Inner Adjustable Clutch
GP-862H



• Inner Adjustable Clutch
GP-862H1

AIR ANGLE SCREWDRIVER (Slip-Clutch Type)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max Torque ft.lb (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-802L90	5.0 ~ 6.0	1/4"	1,600	3.0 (4)	0.90	230	0.28	1/4"	5.0	80	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-804L90	3.0 ~ 4.0	1/4"	1,400	2.2 (3)	0.90	230	0.28	1/4"	5.0	80	< 2.5	20 pcs/1.40 cu-ft/G.W.: 19 kgs
GP-861J	4.0	1/4"	1,800	9.58 (13)	1.10	210	0.73	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 14 kgs
GP-861J1	5.0	1/4"	800	12 (16.38)	1.26	230	0.73	1/4"	6.5	92	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs
GP-862H	4.0	1/4"	1,800	9.58 (13)	1.10	210	0.63	1/4"	6.5	96	< 2.5	10 pcs/0.98 cu-ft/G.W.: 14 kgs
GP-862H1	5.0	1/4"	800	12 (16.38)	1.26	230	0.56	1/4"	6.5	88	< 2.5	10 pcs/0.98 cu-ft/G.W.: 15 kgs



AIR ANGLE SCREWDRIVER (Impact Type)



• Stubby Type
GP-801LA



GP-950



AIR SCREWDRIVER KITS



**GP-861JK
GP-861J1K**



**GP-862HK
GP-862H1K**

AIR ANGLE SCREWDRIVER (Impact Type)

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Capacity (mm)	Shank Size	Free Speed (rpm)	Max. Torque ft.lb (Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-801LA	4.0 ~ 5.0	1/4"	13,000	26 (35)	0.90	150	0.42	1/4"	6.5	88	< 2.5	10 pcs/0.80 cu-ft/G.W.: 11.8 kgs
GP-950	6.0 ~ 8.0	1/4"	10,000	135 (183)	0.95	135	0.42	1/4"	6.5	88	< 2.5	20 pcs/1.70 cu-ft/G.W.: 21 kgs

AIR SCREWDRIVER KITS

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

GP-861JK / GP-861J1K				GP-862HK / GP-862H1K			
1 pc	Air Screwdriver (GP-861JK / GP861J1K)			1 pc	Screwdriver (GP-862HK / GP-862H1K)		
7 pcs	Screw Bits			7 pcs	Screw Bits		
2 pcs	Cap Spanner			2 pcs	Cap Spanner		
1 pc	Plastic Box			1 pc	Plastic Box		
Packing	5 sets/0.98 cu-ft/G.W.: 10 kgs			Packing	5 sets/0.98 cu-ft/G.W.: 10 kgs		