



# AIR IMPACT WRENCH 1-1/2" , 1"



- Handle Exhaust
- Twin Hammer

**GW-36T**



- Front Exhaust
- Pin Hammer

**GW-38P**



- Handle Exhaust
- Twin Hammer

**GW-38TP**



- Twin Hammer

**GW-40TP**



- Twin Hammer

**GW-40J**



- Twin Hammer

**GW-55T**



- Pin Hammer

**GW-38L**



- One Hammer

**GW-45DL**



- Pin Hammer

**GW-45L**



- Twin Hammer

**GW-65**

## AIR IMPACT WRENCH 1-1/2" , 1"

## Specifications

Recommended Air Pressure 115 psi (8 kg/cm<sup>2</sup>)

| Model    | Square Drive | Bolt Capacity (mm) | Max. Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism   | Packing                         |
|----------|--------------|--------------------|------------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|-------------|---------------------------------|
| GW-36T   | 1"           | 38                 | 1,400 (1,900)          | 5.10             | 222         | 1.07                            | 3/8"      | 10             | 97                   | 6.1                             | Twin Hammer | 4 pcs/0.85 cu-ft/G.W.: 23 kgs   |
| GW-38P   | 1"           | 40                 | 1,500 (2,034)          | 10.20            | 270         | 1.35                            | 3/8"      | 13             | 93                   | 7.5                             | Pin Hammer  | 2 pcs/0.92 cu-ft/G.W.: 22 kgs   |
| GW-38TP  | 1"           | 48                 | 2,000 (2,712)          | 9.60             | 300         | 2.21                            | 1/2"      | 13             | 96                   | 7.4                             | Twin Hammer | 2 pcs/1.35 cu-ft/G.W.: 20.6 kgs |
| GW-40TP  | 1"           | 48                 | 2,200 (2,983)          | 10.70            | 536         | 2.41                            | 1/2"      | 13             | 95                   | 6.9                             | Twin Hammer | 2 pcs/1.47 cu-ft/G.W.: 23.7 kgs |
| GW-40J   | 1"           | 48                 | 2,200 (2,983)          | 11.70            | 550         | 2.21                            | 1/2"      | 13             | 102                  | 7.0                             | Twin Hammer | 2 pcs/1.6 cu-ft/G.W.: 26.2 kgs  |
| GW-55T   | 1"           | 50                 | 2,500 (3,390)          | 16.40            | 628         | 1.41                            | 1/2"      | 13             | 104                  | 7.2                             | Twin Hammer | 1 pc/1 cu-ft/G.W.: 18 kgs       |
| *GW-38L  | 1"           | 40                 | 1,500 (2,034)          | 12.50            | 570         | 1.30                            | 3/8"      | 13             | 96                   | 8.2                             | Pin Hammer  | 2 pcs/1.5 cu-ft/G.W.: 27.5 kgs  |
| *GW-45DL | 1"           | 48                 | 2,000 (2,712)          | 16.50            | 595         | 1.30                            | 3/8"      | 13             | 98                   | 5.5                             | One Hammer  | 1 pc/1.0 cu-ft/G.W.: 18 kgs     |
| *GW-45L  | 1"           | 48                 | 2,000 (2,712)          | 16.50            | 595         | 1.30                            | 3/8"      | 13             | 95                   | 5.5                             | Pin Hammer  | 1 pc/1.0 cu-ft/G.W.: 18 kgs     |
| GW-65    | 1-1/2"       | 48-80              | 3,000 (4,068)          | 15.70            | 368         | 1.97                            | 1/2"      | 19             | 98                   | 11.0                            | Twin Hammer | 1 pc/0.85 cu-ft/G.W.: 17.5 kgs  |

\* Inner Trigger Available

Both short and Long Anvil are available for above models.



# AIR IMPACT WRENCH 3/4"



• Pin Clutch  
**GW-22N1**



• Pin Clutch  
**GW-24D**



• Handle Exhaust  
• Twin Hammer  
**GW-24B**



• Twin Hammer  
**GW-26**



• Handle Exhaust  
• Twin Hammer  
**GW-22T**



• Handle Exhaust  
• Twin Hammer  
**GW-23T2**



• Handle Exhaust  
• Twin Hammer  
**GW-24T**



• Handle Exhaust  
• Twin Hammer  
**GW-25T**

## AIR IMPACT WRENCH 3/4"

## Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model   | Square Drive | Bolt Capacity (mm) | Max.Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism   | Packing                         |
|---------|--------------|--------------------|-----------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|-------------|---------------------------------|
| GW-22N1 | 3/4"         | 25                 | 700 (950)             | 4.80             | 240         | 0.63                            | 1/4"      | 8              | 95                   | 3.4                             | Pin Clutch  | 4 pcs/1.32 cu-ft/G.W.: 22.5 kgs |
| GW-24D  | 3/4"         | 27                 | 800 (1,085)           | 4.90             | 248         | 0.63                            | 1/4"      | 8              | 88                   | 3.5                             | Pin Clutch  | 4 pcs/1.36 cu-ft/G.W.: 22.5 kgs |
| GW-24B  | 3/4"         | 36                 | 1,250 (1,690)         | 4.40             | 216         | 1.57                            | 3/8"      | 10             | 96                   | 5.5                             | Twin Hammer | 4 pcs/1.23 cu-ft/G.W.: 20.3 kgs |
| GW-26   | 3/4"         | 32                 | 800 (1,085)           | 5.50             | 310         | 0.80                            | 3/8"      | 8              | 98                   | 3.6                             | Twin Hammer | 4 pcs/0.85 cu-ft/G.W.: 24 kgs   |
| GW-22T  | 3/4"         | 29                 | 800 (1,085)           | 2.50             | 170         | 0.56                            | 1/4"      | 10             | 87                   | 4.5                             | Twin Hammer | 6 pcs/0.7 cu-ft/G.W.: 17 kgs    |
| GW-23T2 | 3/4"         | 32                 | 1,000 (1,356)         | 2.64             | 177         | 0.23                            | 1/4"      | 10             | 87                   | 4.5                             | Twin Hammer | 6 pcs/0.7 cu-ft/G.W.: 18 kgs    |
| GW-24T  | 3/4"         | 36                 | 1,000 (1,356)         | 4.15             | 207         | 0.70                            | 1/4"      | 10             | 94                   | 5.3                             | Twin Hammer | 4 pcs/0.85 cu-ft/G.W.: 18.6 kgs |
| GW-25T  | 3/4"         | 38                 | 1,400 (1,900)         | 5.00             | 215         | 1.07                            | 3/8"      | 10             | 97                   | 6.1                             | Twin Hammer | 4 pcs/0.85 cu-ft/G.W.: 23 kgs   |



# AIR IMPACT WRENCH 1/2"



• One Hammer  
**GW-15B**



• Pin Clutch  
**GW-16H1**



• Pin Clutch  
**GW-18D**



• Twin Hammer  
**GW-19J**



• Handle Exhaust  
• Twin Hammer  
**GW-19JR**



• Twin Hammer  
**GW-19D**



• Handle Exhaust  
• Twin Hammer  
**GW-19S**



• Handle Exhaust  
• Twin Hammer  
**GW-17Y**



• Handle Exhaust  
• Twin Hammer  
**GW-19R**

## AIR IMPACT WRENCH 1/2"

## Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model   | Square Drive | Bolt Capacity (mm) | Max. Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism   | Packing                         |
|---------|--------------|--------------------|------------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|-------------|---------------------------------|
| GW-15B  | 1/2"         | 16                 | 230 (312)              | 2.45             | 178         | 0.62                            | 1/4"      | 6.5            | 98                   | 4.1                             | One Hammer  | 10 pcs/1.5 cu-ft/G.W.: 25 kgs   |
| GW-16H1 | 1/2"         | 16                 | 280 (380)              | 2.30             | 180         | 0.62                            | 1/4"      | 6.5            | 96                   | 2.9                             | Pin Clutch  | 10 pcs/1.34 cu-ft/G.W.: 25 kgs  |
| GW-18D  | 1/2"         | 16                 | 450 (610)              | 2.70             | 190         | 0.62                            | 1/4"      | 6.5            | 88                   | 2.8                             | Pin Clutch  | 8 pcs/1.28 cu-ft/G.W.: 23.6 kgs |
| GW-19J  | 1/2"         | 18                 | 550 (745)              | 2.60             | 188         | 0.63                            | 1/4"      | 6.5            | 94                   | 3.2                             | Twin Hammer | 10 pcs/1.5 cu-ft/G.W.: 30 kgs   |
| GW-19JR | 1/2"         | 18                 | 450 (610)              | 2.60             | 188         | 0.63                            | 1/4"      | 6.5            | 91                   | 3.2                             | Twin Hammer | 10 pcs/1.6 cu-ft/G.W.: 30 kgs   |
| GW-19D  | 1/2"         | 16                 | 400 (543)              | 2.55             | 185         | 0.71                            | 1/4"      | 6.5            | 98                   | 4.8                             | Twin Hammer | 6 pcs/0.7 cu-ft/G.W.: 17.8 kgs  |
| GW-19S  | 1/2"         | 16                 | 460 (626)              | 2.60             | 185         | 0.78                            | 1/4"      | 6.5            | 79                   | 4.5                             | Twin Hammer | 6 pcs/0.8 cu-ft/G.W.: 18.4 kgs  |
| GW-17Y  | 1/2"         | 19                 | 460 (626)              | 1.45             | 123         | 0.71                            | 1/4"      | 6.5            | 95                   | 2.8                             | Twin Hammer | 10 pcs/1.0 cu-ft/G.W.: 17 kgs   |
| GW-19R  | 1/2"         | 18                 | 430 (588)              | 2.67             | 175         | 0.68                            | 1/4"      | 6.5            | 83                   | 2.7                             | Twin Hammer | 8 pcs/1.3 cu-ft/G.W.: 24.5 kgs  |



- Handle Exhaust
  - Twin Hammer
- GW-20T**



- Twin Hammer
- GW-23T1**



- Handle Exhaust
  - Jumbo Hammer
- GW-17J1**



- Handle Exhaust
  - Twin Hammer
- GW-17T1**



- Handle Exhaust
  - Twin Hammer
- GW-17T2**



- Handle Exhaust
  - Jumbo Hammer
- GW-17J**



- Handle Exhaust
  - Twin Hammer
- GW-17T**

## AIR IMPACT WRENCH 1/2"

## Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model   | Square Drive | Bolt Capacity (mm) | Max. Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism    | Packing                      |
|---------|--------------|--------------------|------------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|--------------|------------------------------|
| GW-20T  | 1/2"         | 27                 | 600 (814)              | 2.50             | 164         | 0.20                            | 1/4"      | 6.5            | 92                   | 2.8                             | Twin Hammer  | 6 pcs/0.7 cu-ft/G.W.:18 kgs  |
| GW-23T1 | 1/2"         | 29                 | 1,000 (1356)           | 2.60             | 171         | 0.23                            | 1/4"      | 6.5            | 87                   | 4.5                             | Twin Hammer  | 6 pcs/0.7 cu-ft/G.W.:18 kgs  |
| GW-17J1 | 1/2"         | 16                 | 500 (678)              | 1.40             | 99          | 0.20                            | 1/4"      | 6.5            | 92                   | 2.8                             | Jumbo Hammer | 10 pcs/0.9 cu-ft/G.W.:16 kgs |
| GW-17T1 | 1/2"         | 16                 | 500 (678)              | 1.42             | 108         | 0.20                            | 1/4"      | 6.5            | 92                   | 2.8                             | Twin Hammer  | 10 pcs/0.9 cu-ft/G.W.:16 kgs |
| GW-17T2 | 1/2"         | 16                 | 450 (610)              | 1.40             | 103         | 0.20                            | 1/4"      | 6.5            | 92                   | 2.8                             | Twin Hammer  | 10 pcs/0.9 cu-ft/G.W.:16 kgs |
| GW-17J  | 1/2"         | 16                 | 300 (407)              | 1.35             | 135         | 0.56                            | 1/4"      | 6.5            | 86                   | 2.7                             | Jumbo Hammer | 10 pcs/0.7 cu-ft/G.W.:16 kgs |
| GW-17T  | 1/2"         | 19                 | 460 (626)              | 1.45             | 123         | 0.71                            | 1/4"      | 6.5            | 95                   | 2.8                             | Twin Hammer  | 10 pcs/1.0 cu-ft/G.W.:17 kgs |



# AIR IMPACT WRENCH 3/8"



• One Hammer  
**GW-8**



• Two Hammer  
**GW-12**



• Jumbo Hammer  
**GW-13J1**



• Twin Hammer  
**GW-13T1**



• Twin Hammer  
**GW-13T2**



• Handle Exhaust  
• Jumbo Hammer  
**GW-13J**



• Handle Exhaust  
• Two Hammer  
**GW-13T**



• Handle Exhaust  
• Two Hammer  
**GW-13Y**



• Two Hammer  
**GP-867W**

## AIR IMPACT WRENCH 3/8"

## Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model   | Square Drive | Bolt Capacity (mm) | Max. Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism    | Packing                          |
|---------|--------------|--------------------|------------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|--------------|----------------------------------|
| GW-8    | 3/8"         | 10                 | 75 (102)               | 1.04             | 158         | 0.42                            | 1/4"      | 6.5            | 97                   | < 2.5                           | One Hammer   | 20 pcs/1.91 cu-ft/G.W.: 22 kgs   |
| GW-12   | 3/8"         | 13                 | 135 (183)              | 0.95             | 135         | 0.56                            | 1/4"      | 6.5            | 88                   | 4.5                             | Two Hammer   | 20 pcs/1.2 cu-ft/G.W.: 21 kgs    |
| GW-13J1 | 3/8"         | 16                 | 450 (610)              | 1.40             | 99          | 0.20                            | 1/4"      | 6.5            | 92                   | 3.1                             | Jumbo Hammer | 10 pcs/0.9 cu-ft/G.W.: 16 kgs    |
| GW-13T1 | 3/8"         | 16                 | 450 (610)              | 1.42             | 108         | 0.20                            | 1/4"      | 6.5            | 92                   | 3.1                             | Twin Hammer  | 10 pcs/0.9 cu-ft/G.W.: 16 kgs    |
| GW-13T2 | 3/8"         | 16                 | 400 (542)              | 1.40             | 103         | 0.20                            | 1/4"      | 6.5            | 92                   | 3.1                             | Twin Hammer  | 10 pcs/0.9 cu-ft/G.W.: 16 kgs    |
| GW-13J  | 3/8"         | 14                 | 300 (407)              | 1.35             | 135         | 0.56                            | 1/4"      | 6.5            | 86                   | 2.7                             | Jumbo Hammer | 10 pcs/0.7 cu-ft/G.W.: 16 kgs    |
| GW-13T  | 3/8"         | 14                 | 350 (475)              | 1.50             | 142         | 0.71                            | 1/4"      | 6.5            | 85                   | 2.7                             | Twin Hammer  | 10 pcs/0.7 cu-ft/G.W.: 17 kgs    |
| GW-13Y  | 3/8"         | 16                 | 460 (626)              | 1.45             | 123         | 0.71                            | 1/4"      | 6.5            | 95                   | 2.8                             | Twin Hammer  | 10 pcs/1.0 cu-ft/G.W.: 17 kgs    |
| GP-867W | 3/8"         | 10                 | 150 (203)              | 1.12             | 215         | 0.49                            | 1/4"      | 6.5            | 90                   | 5.4                             | Two Hammer   | 20 pcs/1.44 cu-ft/G.W.: 24.5 kgs |



## COMPOSITE AIR IMPACT WRENCH



- Handle Exhaust
  - Twin Hammer
- GW-13JH**



- Handle Exhaust
  - Twin Hammer
- GW-17JH**



- Handle Exhaust
  - Twin Hammer
- GW-21J**



- Handle Exhaust
  - Twin Hammer
- GW-23J**



- Handle Exhaust
  - Twin Hammer
- GW-28J**



- Handle Exhaust
  - Twin Hammer
- GW-38J**

### COMPOSITE AIR IMPACT WRENCH

### Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model   | Square Drive | Bolt Capacity (mm) | Max.Torque ft.lb (Nm) | Net Weight (kgs) | Length (mm) | Air Cons. (m <sup>3</sup> /min) | Air Inlet | Hose Size (mm) | Sound Pressure (dBA) | Vibration (m/sec <sup>2</sup> ) | Mechanism   | Packing                         |
|---------|--------------|--------------------|-----------------------|------------------|-------------|---------------------------------|-----------|----------------|----------------------|---------------------------------|-------------|---------------------------------|
| GW-13JH | 3/8"         | 16                 | 450 (610)             | 1.30             | 160         | 0.84                            | 1/4"      | 8              | 89                   | 4.8                             | Twin Hammer | 10 pcs/0.9 cu-ft/G.W.: 15.3 kgs |
| GW17JH  | 1/2"         | 18                 | 550 (745)             | 1.30             | 160         | 0.84                            | 1/4"      | 8              | 85                   | 4.6                             | Twin Hammer | 10 pcs/1.6 cu-ft/G.W.: 24.5 kgs |
| GW-21J  | 1/2"         | 27                 | 820 (1,110)           | 2.10             | 190         | 0.99                            | 1/4"      | 8              | 91                   | 8.1                             | Twin Hammer | 10 pcs/1.6 cu-ft/G.W.: 24.5 kgs |
| GW-23J  | 3/4"         | 27                 | 820 (1,110)           | 2.30             | 195         | 0.99                            | 1/4"      | 8              | 91                   | 8.1                             | Twin Hammer | 10 pcs/0.9 cu-ft/G.W.: 15.7 kgs |
| GW-28J  | 3/4"         | 38                 | 1,500 (2,034)         | 3.70             | 220         | 1.41                            | 3/8"      | 13             | 97                   | 8.6                             | Twin Hammer | 6 pcs/1.3 cu-ft/G.W.: 24.3 kgs  |
| GW-38J  | 1"           | 38                 | 1,500 (2,034)         | 3.80             | 230         | 1.41                            | 3/8"      | 13             | 97                   | 8.6                             | Twin Hammer | 6 pcs/1.3 cu-ft/G.W.: 24.9 kgs  |



# AIR RATCHET WRENCH 1/2", 3/8"



• Stubby Type  
**GP-855H**



**GP-855F**



**GP-855B 3/8"**  
**GP-856B 1/2"**



**GP-855D 3/8"**  
**GP-856D 1/2"**



• Low Recoil  
**GP-855G 3/8"**  
**GP-856G 1/2"**



**GP-855GR 3/8"**  
**GP-856GR 1/2"**



• Low Recoil  
**GP-855J2 3/8"**  
**GP-856J2 1/2"**



• Quick Change Socket  
**GP-855Q 3/8"**  
**GP-856Q 1/2"**



**GP-857**

## AIR RATCHET WRENCH 1/2", 3/8"

## Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model    | Square Drive | Max.Torque<br>ft.lb (Nm) | Net Weight<br>(kgs) | Length<br>(mm) | Air Cons.<br>(m <sup>3</sup> /min) | Air Inlet | Hose Size<br>(mm) | Sound Pressure<br>(dBA) | Vibration<br>(m/sec <sup>2</sup> ) | Packing                         |
|----------|--------------|--------------------------|---------------------|----------------|------------------------------------|-----------|-------------------|-------------------------|------------------------------------|---------------------------------|
| GP-855H  | 3/8"         | 22 (30)                  | 0.50                | 125            | 0.37                               | 1/4"      | 6.5               | 86                      | < 2.5                              | 30 pcs/0.7 cu-ft/G.W.: 16 kgs   |
| GP-855F  | 3/8"         | 37 (50)                  | 0.64                | 165            | 0.49                               | 1/4"      | 6.5               | 87                      | < 2.5                              | 30 pcs/0.7 cu-ft/G.W.: 21 kgs   |
| GP-855B  | 3/8"         | 50 (68)                  | 0.97                | 254            | 0.54                               | 1/4"      | 6.5               | 98                      | < 2.5                              | 20 pcs/0.7 cu-ft/G.W.: 24 kgs   |
| GP-856B  | 1/2"         | 50 (68)                  | 0.97                | 254            | 0.56                               | 1/4"      | 6.5               | 98                      | < 2.5                              | 20 pcs/0.7 cu-ft/G.W.: 24 kgs   |
| GP-855D  | 3/8"         | 50 (68)                  | 1.20                | 265            | 0.49                               | 1/4"      | 6.5               | 86                      | < 2.5                              | 12 pcs/1.1 cu-ft/G.W.: 16.5 kgs |
| GP-856D  | 1/2"         | 50 (68)                  | 1.20                | 265            | 0.49                               | 1/4"      | 6.5               | 86                      | < 2.5                              | 10 pcs/1.1 cu-ft/G.W.: 16.5 kgs |
| GP-855G  | 3/8"         | 50 (68)                  | 1.30                | 294            | 0.45                               | 1/4"      | 6.5               | 87                      | < 2.5                              | 10 pcs/0.9 cu-ft/G.W.: 15 kgs   |
| GP-856G  | 1/2"         | 50 (68)                  | 1.30                | 294            | 0.45                               | 1/4"      | 6.5               | 87                      | < 2.5                              | 10 pcs/0.9 cu-ft/G.W.: 15 kgs   |
| GP-855GR | 3/8"         | 55 (75)                  | 1.20                | 267            | 0.63                               | 1/4"      | 6.5               | 90                      | < 2.5                              | 20 pcs/1.2 cu-ft/G.W.: 25 kgs   |
| GP-856GR | 1/2"         | 55 (75)                  | 1.20                | 267            | 0.63                               | 1/4"      | 6.5               | 90                      | < 2.5                              | 20 pcs/1.2 cu-ft/G.W.: 25 kgs   |
| GP-855J2 | 3/8"         | 60 (82)                  | 1.30                | 265            | 0.49                               | 1/4"      | 6.5               | 87                      | < 2.5                              | 20 pcs/1.7 cu-ft/G.W.: 30 kgs   |
| GP-856J2 | 1/2"         | 60 (82)                  | 1.20                | 270            | 0.49                               | 1/4"      | 6.5               | 74                      | 3.0                                | 20 pcs/0.66 cu-ft/G.W.: 28 kgs  |
| GP-855Q  | 3/8"         | 60 (82)                  | 1.30                | 254            | 0.63                               | 1/4"      | 6.5               | 95                      | < 2.5                              | 20 pcs/1.2 cu-ft/G.W.: 26 kgs   |
| GP-856Q  | 1/2"         | 60 (82)                  | 1.30                | 254            | 0.63                               | 1/4"      | 6.5               | 95                      | < 2.5                              | 20 pcs/1.2 cu-ft/G.W.: 26 kgs   |
| GP-857   | 1/2"         | 90 (122)                 | 2.00                | 360            | 0.63                               | 1/4"      | 6.5               | 103                     | 5.3                                | 10 pcs/0.57 cu-ft/G.W.: 22 kgs  |



# AIR RATCHET WRENCH 1/4"



## AIR RATCHET WRENCH 1/4"

### Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

| Model    | Square Drive | Max.Torque<br>ft.lb (Nm) | Net Weight<br>(kgs) | Length<br>(mm) | Air Cons.<br>(m <sup>3</sup> /min) | Air Inlet | Hose Size<br>(mm) | Sound Pressure<br>(dBA) | Vibration<br>(m/sec <sup>2</sup> ) | Packing                          |
|----------|--------------|--------------------------|---------------------|----------------|------------------------------------|-----------|-------------------|-------------------------|------------------------------------|----------------------------------|
| GP-854H  | 1/4"         | 22 (30)                  | 0.50                | 125            | 0.37                               | 1/4"      | 6.5               | 86                      | < 2.5                              | 30 pcs/0.7 cu-ft/G.W.: 16 kgs    |
| GP-854F  | 1/4"         | 37 (50)                  | 0.64                | 165            | 0.49                               | 1/4"      | 6.5               | 87                      | < 2.5                              | 30 pcs/0.7 cu-ft/G.W.: 21 kgs    |
| GP-854   | 1/4"         | 30 (40)                  | 0.50                | 170            | 0.49                               | 1/4"      | 6.5               | 90                      | < 2.5                              | 10 pcs/0.5 cu-ft/G.W.: 8 kgs     |
| GP-854D  | 1/4"         | 30 (40)                  | 0.54                | 174            | 0.54                               | 1/4"      | 6.5               | 72                      | < 2.5                              | 20 pcs/0.64 cu-ft/G.W.: 15.9 kgs |
| GP-854J  | 1/4"         | 30 (41)                  | 0.60                | 210            | 0.54                               | 1/4"      | 6.5               | 85                      | < 2.5                              | 20 pcs/1.1 cu-ft/G.W.: 17 kgs    |
| GP-854J2 | 1/4"         | 30 (41)                  | 0.50                | 167            | 0.54                               | 1/4"      | 6.5               | 83                      | < 2.5                              | 20 pcs/1.1 cu-ft/G.W.: 15 kgs    |



## AIR IMPACT WRENCH KITS

**GW-15BK**



**GW-16H1K**



**GW-18DK**



**GW-21JK**



**GW-24DK**



### AIR IMPACT WRENCH KITS

### Specifications

#### GW-15BK

|         |                                 |
|---------|---------------------------------|
| 1 pc    | 1/2" Air Impact Wrench (GW-15B) |
| 10 pcs  | Socket 9 ~ 27 mm                |
| 1 pc    | Extension Bar                   |
| 1 pc    | Nipple                          |
| 1 pc    | Oil Pot                         |
| 1 pc    | Hex. Key Wrench                 |
| 1 pc    | Mini Oiler                      |
| 1 pc    | Plastic Box                     |
| Packing | 5 sets/1.5 cu-ft/G.W.: 22 kgs   |

#### GW-16H1K

|         |                                  |
|---------|----------------------------------|
| 1 pc    | 1/2" Air Impact Wrench (GW-16H1) |
| 10 pcs  | Socket 9 ~ 27 mm                 |
| 1 pc    | Extension Bar                    |
| 1 pc    | Nipple                           |
| 1 pc    | Oil Pot                          |
| 1 pc    | Hex. Key Wrench                  |
| 1 pc    | Mini Oiler                       |
| 1 pc    | Plastic Box                      |
| Packing | 4 sets/1.2 cu-ft/G.W.: 19 kgs    |

#### GW-18DK

|         |                                 |
|---------|---------------------------------|
| 1 pc    | 1/2" Air Impact Wrench (GW-18D) |
| 10 pcs  | Socket 9 ~ 27 mm                |
| 1 pc    | Extension Bar                   |
| 1 pc    | Nipple                          |
| 1 pc    | Oil Pot                         |
| 1 pc    | Hex. Key Wrench                 |
| 1 pc    | Mini Oiler                      |
| 1 pc    | Plastic Box                     |
| Packing | 4 sets/1.51 cu-ft/G.W.: 21 kgs  |

#### GW-21JK

|         |                                           |
|---------|-------------------------------------------|
| 1 pc    | 1/2" Composite Air Impact Wrench (GW-21J) |
| 11 pcs  | Socket 9 ~ 27 mm                          |
| 1 pc    | Extension Bar                             |
| 1 pc    | Universal Joint                           |
| 1 pc    | Oil Pot                                   |
| 1 pc    | 1/4" Air Inlet                            |
| 1 pc    | Plastic Box                               |
| Packing | 5 sets/2.8 cu-ft/G.W.: 26.7 kgs           |

#### GW-24DK

|         |                                  |
|---------|----------------------------------|
| 1 pc    | 3/4" Air Impact Wrench (GW-24D)  |
| 8 pcs   | Socket 26 ~ 38 mm                |
| 1 pc    | Extension Bar                    |
| 1 pc    | Nipple                           |
| 1 pc    | Oil Pot                          |
| 1 pc    | Hex. Key Wrench                  |
| 1 pc    | Plastic Box                      |
| Packing | 2 sets/1.25 cu-ft/G.W.: 21.5 kgs |



## AIR RATCHET WRENCH KITS



**GP-855BK**



**GP-855DK**



**GP-856BK**



**GP-856DK**

### AIR RATCHET WRENCH KITS

### Specifications

| GP-855BK |                                   | GP-855DK |                                   | GP-856BK |                                   |
|----------|-----------------------------------|----------|-----------------------------------|----------|-----------------------------------|
| 1 pc     | 3/8" Air Ratchet Wrench (GP-855B) | 1 pc     | 3/8" Air Ratchet Wrench (GP-855D) | 1 pc     | 1/2" Air Ratchet Wrench (GP-856B) |
| 7 pcs    | Socket                            | 7 pcs    | Socket                            | 7 pcs    | Socket                            |
| 1 pc     | Universal Joint                   | 1 pc     | Universal Joint                   | 1 pc     | Universal Joint                   |
| 2 pcs    | Adapter                           | 1 pc     | 75mm Extension Bar                | 2 pcs    | Adapter                           |
| 1 pc     | Nipple                            | 1 pc     | Nipple                            | 1 pc     | Nipple                            |
| 3 pcs    | Bit                               | 1 pc     | Oil Pot                           | 3 pcs    | Bit                               |
| 1 pc     | Oil Pot                           | 1 pc     | Blow Case                         | 1 pc     | Oiler Pot                         |
| 1 pc     | Plastic Box                       | Packing  | 6 sets/1.3 cu-ft/G.W.: 15 kgs     | 1 pc     | Plastic Box                       |
| Packing  | 5 sets/0.75 cu-ft/G.W.: 13.5 kgs  |          |                                   | Packing  | 5 sets/0.75 cu-ft/G.W.: 13.5 kgs  |
| GP-856DK |                                   |          |                                   |          |                                   |
| 1 pc     | 1/2" Air Ratchet Wrench (GP-856D) |          |                                   |          |                                   |
| 7 pcs    | Socket                            |          |                                   |          |                                   |
| 1 pc     | Universal Joint                   |          |                                   |          |                                   |
| 1 pc     | 75mm Extension Bar                |          |                                   |          |                                   |
| 1 pc     | Nipple                            |          |                                   |          |                                   |
| 1 pc     | Oil Pot                           |          |                                   |          |                                   |
| 1 pc     | Blow Case                         |          |                                   |          |                                   |
| Packing  | 6 sets/1.3 cu-ft/G.W.: 15 kgs     |          |                                   |          |                                   |