



SPRING BALANCER



GP-SB01D
GP-SB01A
GP-SB01B
GP-SB01C



GP-SB01F



GP-SB01J
GP-SB01K



GP-SB01I
GP-SB02I



GP-SB03I
GP-SB04I
GP-SB01GR



GP-SB05I



GP-SB06I
GP-SB07I
GP-SB08I
GP-SB09I
GP-SB10I
GP-SB11I

※ Features

- Keeps working bench in good order.
- Increases working efficiency.
- Helps operator feel less tired and increase safety.

※ Convenient force adjustment by rotary adjustment cap.

※ Special design.

※ Increasing screw diameter is balanced by increasing spring force so that the output force is balanced and the tool stops at wherever it is pulled.

SPRING BALANCER Specifications

Model No.	Capacity (kgs)	Travel (M)	Rope Material	Wire Dia. (mm)	Net Weight (kgs)	Packing
GP-SB01D	0.3 ~ 0.8	1.4	Cable / Nylon	2.5 / 4.0	0.49	40 pcs/1.7 cu-ft/G.W.: 19.8 kgs
GP-SB01A	0.6 ~ 1.5	1.4	Cable / Nylon	2.5 / 4.0	0.52	40 pcs/1.7 cu-ft/G.W.: 21.8 kgs
GP-SB01B	1.0 ~ 2.0	1.4	Cable / Nylon	2.5 / 4.0	0.53	40 pcs/1.7 cu-ft/G.W.: 22.4 kgs
GP-SB01C	1.5 ~ 3.0	1.5	Cable	3.2	0.76	30 pcs/1.6 cu-ft/G.W.: 22.8 kgs
GP-SB01F	3.0 ~ 5.0	1.5	Cable	3.2	0.81	30 pcs/1.6 cu-ft/G.W.: 24.1 kgs
GP-SB01J	0.3 ~ 1.2	1.6	Nylon	4.0	0.57	30 pcs/1.6 cu-ft/G.W.: 18.7 kgs
GP-SB01K	0.8 ~ 2.0	1.6	Nylon	4.0	0.57	30 pcs/1.6 cu-ft/G.W.: 20.1 kgs
GP-SB01I	9.0 ~ 15.0	1.3	Cable	4.7	3.61	4 pcs/1.9 cu-ft/G.W.: 15.44 kgs
GP-SB02I	5.0 ~ 9.0	1.3	Cable	4.7	3.59	4 pcs/1.9 cu-ft/G.W.: 14.9 kgs
GP-SB01GR	5.0 ~ 7.0	1.3	Cable	3.2	1.85	10 pcs/1.7 cu-ft/G.W.: 20.9 kgs
GP-SB03I	3.0 ~ 5.0	1.3	Cable	3.2	1.82	10 pcs/1.7 cu-ft/G.W.: 19.2 kgs
GP-SB04I	1.5 ~ 3.0	1.3	Cable	3.2	1.73	10 pcs/1.7 cu-ft/G.W.: 18.3 kgs
GP-SB05I	0.5 ~ 1.5	1.3	Cable	2.0	0.73	20 pcs/1.9 cu-ft/G.W.: 15.6 kgs
GP-SB06I	15 ~ 22	1.5	Cable	4.8	7.10	1 pc/0.6 cu-ft/G.W.: 7.7 kgs
GP-SB07I	22 ~ 30	1.5	Cable	4.8	7.60	1 pc/0.6 cu-ft/G.W.: 8.3 kgs
GP-SB08I	30 ~ 40	1.5	Cable	4.8	9.70	1 pc/0.9 cu-ft/G.W.: 11 kgs
GP-SB09I	40 ~ 50	1.5	Cable	4.8	10.10	1 pc/0.9 cu-ft/G.W.: 11.4 kgs
GP-SB10I	50 ~ 60	1.5	Cable	4.8	11.10	1 pc/0.9 cu-ft/G.W.: 12.4 kgs
GP-SB11I	60 ~ 70	1.5	Cable	4.8	11.40	1 pc/0.9 cu-ft/G.W.: 12.7 kgs



AIR HOSE BALANCER



GP-RB02/RB02B



GP-AB02A/B/C



GP-AB03A/B/C/D/E



AIR HOSE REEL



GP-RB01A/B



GP-RB05A/B/C/D



GP-RB03A/B/C/D

※ Features

- PU braid hose carries long duration and cold resistance yet light weight.
- Excellent flexibility resists pressure from passing cars while working on the road.
- 360° swivel base and long hose allow operation in wide range.

AIR HOSE BALANCER

Specifications

Hose Material : Polyurethane

Model No.	Capacity (kg)	Hose Size (mm)	Hose Length (M)	Air Inlet	Net Weight (kgs)	Case Size (mm)	Working Pressure psi (kg/cm ²)	Break Pressure psi (kg/cm ²)	Packing
GP-RB02	0.6 ~ 1.5	5 x 8	1.2	1/4"	0.86	205 x 155 x 105	100 (7)	400 (28)	10 pcs/1.4 cu-ft/G.W.: 11 kgs
GP-RB02B	0.6 ~ 1.5	5 x 8	2.0	1/4"	0.90	205 x 155 x 105	100 (7)	400 (28)	10 pcs/1.4 cu-ft/G.W.: 11 kgs
GP-AB02A	0.5 ~ 1.5	6.5 x 10	1.4	1/4"	1.80	344 x 190 x 80	145 (10)	900 (63)	6 pcs/1.9 cu-ft/G.W.: 11.7 kgs
GP-AB02B	1.5 ~ 3.0	6.5 x 10	1.4	1/4"	1.90	344 x 190 x 80	145 (10)	900 (63)	6 pcs/1.9 cu-ft/G.W.: 12.4 kgs
GP-AB02C	3.0 ~ 5.0	6.5 x 10	1.4	1/4"	2.00	344 x 190 x 80	145 (10)	900 (63)	6 pcs/1.9 cu-ft/G.W.: 13.0 kgs
GP-AB03A	0.5 ~ 1.5	8 x 12	1.3	3/8"	2.20	288 x 188.5 x 143.5	145 (10)	900 (63)	6 pcs/2.5 cu-ft/G.W.: 14.8 kgs
GP-AB03B	1.5 ~ 2.5	8 x 12	1.3	3/8"	2.30	288 x 188.5 x 143.5	145 (10)	900 (63)	6 pcs/2.5 cu-ft/G.W.: 15.4 kgs
GP-AB03C	2.5 ~ 3.5	8 x 12	1.3	3/8"	2.40	288 x 188.5 x 143.5	145 (10)	900 (63)	6 pcs/2.5 cu-ft/G.W.: 16 kgs
GP-AB03D	3.5 ~ 5.0	8 x 12	1.3	3/8"	2.40	288 x 188.5 x 143.5	145 (10)	900 (63)	6 pcs/2.5 cu-ft/G.W.: 16 kgs
GP-AB03E	5.0 ~ 6.5	8 x 12	1.3	3/8"	2.50	288 x 188.5 x 143.5	145 (10)	900 (63)	6 pcs/2.5 cu-ft/G.W.: 16.6 kgs

AIR HOSE REEL

Specifications

Hose Material : Polyurethane Braid

Model No.	Hose Size (mm)	Hose Length (M)	Air Inlet	Net Weight (kgs)	Case Size (mm)	Working Pressure psi (kg/cm ²)	Break Pressure psi (kg/cm ²)	Packing
GP-RB01A	5 x 8	7.5	1/4"	1.4	240 x 215 x 95	100 (7)	350 (24)	10 pcs/2.0 cu-ft/G.W.: 20 kgs
GP-RB01B	6.5 x 10	6.0	1/4"	1.4	240 x 215 x 95	100 (7)	350 (24)	10 pcs/2.0 cu-ft/G.W.: 20 kgs
GP-RB05A	6.5 x 10	8	1/4"	2.8	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G.W.: 22 kgs
GP-RB05B	6.5 x 10	10	1/4"	2.9	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G.W.: 22 kgs
GP-RB05C	6.5 x 10	12	1/4"	3.0	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G.W.: 22 kgs
GP-RB05D	8 x 12	8	1/4"	2.9	345 x 300 x 145	200 (14)	800 (55)	6 pcs/4.2 cu-ft/G.W.: 22 kgs
GP-RB03A	6.5 x 10	30	1/4"	7.5	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 17 kgs
GP-RB03B	6.5 x 10	50	1/4"	9.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 20 kgs
GP-RB03C	8.5 x 12.5	30	1/4"	8.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 17 kgs
GP-RB03D	8.5 x 12.5	40	1/4"	9.0	350 x 290 x 390	220 (15)	870 (60)	2 pcs/2.9 cu-ft/G.W.: 18 kgs